3GTR完了済製品一覧(メーカブランド通信モジュール)

改訂日：2023/2/10

©2001-2023 NTT DOCOMO, INC. All Rights Reserved.

型番	メーカー名	Features	3GTR完了年度	RAT	Form Factor	chipset		Photo	Module Firmware Version	UMTS					GSM				LTE					Interface	Class		Category			CA (Carrier aggregation)	GPS		Operating Temperature	Dimension W×L×H×H(mm)	Weight(g)	Voice or Data	Website	お問い合わせ先		
						Manufacturer	Model name			Band I (2G)	Band VI (800M)	Band IX (1.7G)	Band V (850M)	Band XIX (800M)	GSM900	GSM1800	PCS1900	GSM US850	Band1 (2G)	Band3 (1.7G)	Band17 (700M)	Band19 (800M)	Band21 (1.5G)	Band28 (700M)		GPRS	EDGE	UMTS Downlink	UMTS Uplink	LTE		Standalone	Assisted (Control Plane)						メーカー	部署／担当者	電話番号
WLWHQ10	AGKEY Computer Corporation	Support LTE/3G data connection D/L 100Mbps, U/L 50Mbps Three U.FL Antenna Connection Option support SMS, A-GPS	2013年度	LTE/UMTS	Mini PCI Express	Qualcomm	MDM9215		1.0.00	S	S	NS	S	S	NS	NS	NS	NS	S	NS	NS	S	S	NS	USB 2.0 x 1	NS	NS	Cat 24	Cat 6	Cat 3	NS	S	S	-20℃ - +60℃ (Extend to 70℃)	30 x 26.8 x 3.9	about 6.5	Data	http://www.agkey.com.tw	AGKEY Computer Corporation	Marketing Division 3/ Stella Liao	+886-2-2228-7588#18625
WLWNQ20	AGKEY Computer Corporation	Support LTE/3G data connection D/L 150Mbps, U/L 50Mbps Three IPEX MHF4 Antenna Connection Option support SMS, A-GPS	2014年度	LTE/UMTS	M.2	Qualcomm	MDM9229M		1.0.00, 2.0.01	S	S	NS	S	S	NS	NS	NS	NS	S	S	NS	S	S	NS	USB 2.0 x 1	NS	NS	Cat 24	Cat 6	Cat 4	NS	S	S	-20℃ - +60℃ (Extend to 70℃)	30 x 42 x 2.3	about 6	Data	http://www.agkey.com.tw	AGKEY Computer Corporation	Marketing Division 3/ Stella Liao	+886-2-2228-7588#18625
WLWHQ20	AGKEY Computer Corporation	Support LTE FDD, CA/3G data connection D/L 300Mbps, U/L 100Mbps Five IPEX Antenna Connectors Option support SMS, A-GPS	2016年度	LTE/UMTS	Mini PCI Express	Qualcomm	MDM9230		1.0.00	S	S	NS	NS	NS	NS	NS	NS	NS	S	S	NS	S	S	NS	USB 2.0 x 1	NS	NS	Cat 24	Cat 6	Cat 6	S	S	S	-20℃ - + 70℃	30x50.95x4	about 7.5	Data	http://www.agkey.com.tw	AGKEY Computer Corporation	Marketing Division 3/ Stella Liao	+886-2-2228-7588#18625
EM7330	Sierra Wireless	Designed to be Windows 8 Mobile Broadband Interface Model (MBIM) compliant.	2013年度	LTE/UMTS	M.2	Qualcomm	MDM9215		05.05.65.00	S	S	NS	NS	S	S	S	S	S	S	NS	NS	S	S	NS	USB 2.0 x 1	10	12	Cat.10	Cat 6	Cat 3	NS	S	NS	-30℃ to +75℃	42 x 30 x 2.39	6	DATA	http://www.sierrawireless.com/productsandservices/AirPrime_Wireless_Modules/Essential_Modules/EM_Series.aspx	Sierra Wireless Japan K.K	Sales／Hidekazu Horiawa	+81-3-6717-6030
MC7330	Sierra Wireless	Designed to be Windows 8 Mobile Broadband Interface Model (MBIM) compliant.	2013年度	LTE/UMTS	Mini PCI Express	Qualcomm	MDM9215		05.05.65.00	S	S	NS	S	S	S	S	S	S	S	NS	NS	S	S	NS	USB 2.0 x 1	10	12	Cat 10	Cat 6	Cat 3	NS	S	NS	-40℃ to +85℃	50.95 x 30 x 2.75	8.6	DATA	http://www.sierrawireless.com/productsandservices/AirPrime_Wireless_Modules/Essential_Modules/MC_Series.aspx	Sierra Wireless Japan K.K	Sales／Hidekazu Horiawa	+81-3-6717-6030
EM7340	Sierra Wireless	Designed to be Windows 8 Mobile Broadband Interface Model (MBIM) compliant.	2014年度	LTE/UMTS	M.2	Intel	XG716 + S4G		FW7360_V1.3_AP_01.3644.02_2_P	S	S	NS	NS	NS	S	S	NS	NS	S	S	NS	S	S	NS	USB 2.0 x 1	NS	NS	Cat 10	Cat 6	Cat 4	NS	S	NS	-10℃ to +70℃	42 x 30 x 2.39	6	DATA	http://www.sierrawireless.com/productsandservices/AirPrime_Wireless_Modules/Essential_Modules/EM_Series.aspx	Sierra Wireless Japan K.K	Sales／Hidekazu Horiawa	+81-3-6717-6030
HL6 3G 850	Sierra Wireless	Smallest HSDPA module, low power consumption.	2014年度	UMTS Only	Original 40 pin connector	Qualcomm	QSC6270		001.90	S	S	NS	NS	NS	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	12	12	Cat 6	384K	NS	NS	NS	NS	-40℃ - +85℃	27 x 27 x 4.8	6.6	DATA	http://developer.sierrawireless.com/Resources/Resources/Gagemcom#GM/Hilus/Hilus_3G_Technical_Specifications.aspx	Sierra Wireless Japan K.K	Sales／Hidekazu Horiawa	+81-3-6717-6030
SL8084T	Sierra Wireless	For M2M soldered-down module.Supporting the Open AT Application Framework.	2014年度	UMTS Only	74 pin LGA	Qualcomm	QSC6270		S4.1.0.21, C04.05.14.00	S	S	NS	S	S	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	10	12	Cat 6	384K	NS	NS	S	NS	-40℃ to +85℃	30 x 25 x 2.4	3.5	Voice (3G CS) /Data	http://www.sierrawireless.com/productsandservices/AirPrime_Wireless_Modules/Smart_Modules/SL_Series.aspx	Sierra Wireless Japan K.K	Sales／Hidekazu Horiawa	+81-3-6717-6030
SL8084BT	Sierra Wireless	For M2M soldered-down module.Supporting the Open AT Application Framework.	2014年度	UMTS Only	74 pin LGA	Qualcomm	QSC6270		S4.1.0.21, C04.05.14.00	S	S	NS	S	S	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	10	12	Cat 6	384K	NS	NS	NS	NS	-40℃ to +85℃	30 x 25 x 2.4	3.5	Voice (3G CS) /Data	http://www.sierrawireless.com/productsandservices/AirPrime_Wireless_Modules/Smart_Modules/SL_Series.aspx	Sierra Wireless Japan K.K	Sales／Hidekazu Horiawa	+81-3-6717-6030
HL8548	Sierra Wireless	For M2M soldered-down module	2015年度	UMTS Only	146 pin LGA	Intel	XMM6250		5.5.22.0, 5.5.24.0, 5.5.24.2	S	S	NS	S	S	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	33	33	Cat 8	Cat 6	NS	NS	NS	NS	-40℃ to +85℃	23 x 22 x 2.5	3.5	Voice (3G CS) /Data	http://www.sierrawireless.com/airprime_wireless_modules/essential_modules/hl_series/	Sierra Wireless Japan K.K	Sales／Hidekazu Horiawa	+81-3-6717-6030
HL8548-G	Sierra Wireless	For M2M soldered-down module	2015年度	UMTS Only	146 pin LGA	Intel	XMM6250		5.5.22.0, 5.5.24.0, 5.5.24.2	S	S	NS	S	S	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	33	33	Cat 8	Cat 6	NS	NS	S	NS	-40℃ to +85℃	23 x 22 x 2.5	3.5	Voice (3G CS) /Data	http://www.sierrawireless.com/airprime_wireless_modules/essential_modules/hl_series/	Sierra Wireless Japan K.K	Sales／Hidekazu Horiawa	+81-3-6717-6030
HL7539	Sierra Wireless	For M2M soldered-down module	2015年度	LTE Only	146 pin LGA	Intel	XMM7160		2.7, 2.8, 2.9, 2.11	NS	NS	NS	NS	NS	NS	NS	NS	NS	S	NS	NS	S	S	NS	USB 2.0 x 1 / Serial x 1	NS	NS	NS	NS	S	NS	NS	NS	-40℃ to +85℃	23 x 22 x 2.5	3.5	Data	http://www.sierrawireless.com/airprime_wireless_modules/essential_modules/hl_series/	Sierra Wireless Japan K.K	Sales／Hidekazu Horiawa	+81-3-6717-6030
AR8552	Rolling Wireless S.à r.l.	Automotive-grade LGA soldered-down module.	2019年度	UMTS Only	LGA	Qualcomm	MDM6200		ARx552_02_FP_00.05.18.03 ARx552_02_FP_00.05.18.06	S	S	NS	S	S	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	10	12	Cat 10	Cat 6	NS	NS	S	NS	-40℃ to +85℃	40 x 40 x 4.12	11.8	Voice (3G CS) /Data	http://www.rollingwireless.com/	Rolling Wireless J.P.Limited	System Engineering/Hironobu Sasaki	+81-3-6717-6032
AR7554	Rolling Wireless S.à r.l.	Automotive-grade LGA soldered-down module.	2017年度	LTE/UMTS	LGA	Qualcomm	MDM9215		SW8x5A_07_10.19.00 SW8x5A_07_10.03.02	S	S	NS	NS	NS	NS	NS	NS	NS	S	S	NS	S	S	NS	USB2.0 x1/ UART x 2	NS	NS	Cat 24	Cat 6	Cat.3	NS	S	S	-40℃ to +85℃	37 x 32 x 3.64	9	Voice (VoLTE, 3G CS) /Data	http://www.rollingwireless.com/	Rolling Wireless J.P.Limited	System Engineering/Hironobu Sasaki	+81-3-6717-6032
SEM-820	Wistron NeWeb Corporation	Low power consumption Automotive proven LGA form factor Proven module for smart engery Easy migration to LTE	2013年度	UMTS only	LGA	Qualcomm	MDM9215		CB2-V1.0	S	S	NS	NS	S	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	NS	NS	Cat 8	Cat 6	NS	NS	NS	NS	-30℃ - +85℃	34 x 34 x 3	6	Data	http://www.wnc.com.tw	Wistron NeWeb Corporation	Peggy Chen	+81-8079438910
HC28-J	Telit Wireless Solutions	1.Footprint Compatibility with Global module 2.Extended Temperature range 3.Embedded GPS support 4.MS windows/Linux Support	2011年第10期	UMTS/GSM	original 80pin connector	Qualcomm	MSM6280		2.002	S	S	NS	NS	S	S	NS	NS	NS	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	10	10	Cat 6	384K	NS	NS	S	NS	-30℃ - +85℃	50 x 34.0 x 4.5	10	Voice (3G CS) /Data	None	Telit Wireless Solutions	Sales / Hideyuki Numata	+81-3-5412-7650
PH8-J Rel.2	Telit Wireless Solutions	1.Footprint Compatibility (80pin) 2.Extended Temperature range 3.TCP/IP protocol support 4.Embedded GPS with A-GPS support 5.MS windows/Linux/Android Support	2012年度	UMTS/GSM	original 80pin connector	Qualcomm	MDM6200		2.101	S	S	NS	S	NS	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	12	12	Cat 10	Cat 6	NS	NS	S	S	-40℃ - +85℃	50 x 33.9 x 3.1	9.5	Data	None	Telit Wireless Solutions	Sales / Hideyuki Numata	+81-3-5412-7650
PH8-J Rel.3	Telit Wireless Solutions	1.Footprint Compatibility (80pin) 2.Extended Temperature range 3.Embedded SIM 4.Embedded GPS with A-GPS support 5.MS windows/Linux/Android Support	2012年度	UMTS/GSM	original 80pin connector	Qualcomm	MDM6200		3.001	S	S	NS	S	NS	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	12	12	Cat 10	Cat 6	NS	NS	S	S	-40℃ - +85℃	50 x 33.9 x 3.1	9.5	Voice (3G CS) /Data	None	Telit Wireless Solutions	Sales / Hideyuki Numata	+81-3-5412-7650
PHS8-J Rel.3	Telit Wireless Solutions	1.Footprint Compatibility (LGA-156pad) 2.Extended Temperature range 3.Support Embedded SIM 4.Embedded GPS with A-GPS support 5.MS windows/Linux/Android Support	2012年度	UMTS/GSM	LGA	Qualcomm	MDM6200		3.001	S	S	NS	S	NS	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	12	12	Cat 10	Cat 6	NS	NS	S	S	-40℃ - +85℃	29 x 33 x 2	5	Voice (3G CS) /Data	None	Telit Wireless Solutions	Sales / Hideyuki Numata	+81-3-5412-7650
EHS6	Telit Wireless Solutions	1.Footprint Compatibility (LGA-116pad) 2.Extended Temperature range 3.Support Embedded SIM 4.Java ME support 5.MS windows/Linux/Android Support	2015年度	UMTS/GSM	LGA	INTEL	XMM6250		3.001 4.003	S	S	NS	S	NS	S	S	S	S	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 2	12	12	Cat 8	Cat 6	NS	NS	NS	NS	-40℃ - + 85℃	25.4 x 27.6 x 2.2	3.5	Data	https://www.gemalto.com/iot/iot-connectivity/products/iot-modules/ehs6	Telit Wireless Solutions	Sales / Hideyuki Numata	+81-3-5412-7650
PDS6-J	Telit Wireless Solutions	1.Footprint Compatibility (LGA-116pad) 2.Extended Temperature range 3.Support Embedded SIM 4.Java ME support 5.MS windows/Linux/Android Support	2015年度	UMTS/GSM	LGA	INTEL	XMM6250		3.001 4.003	S	S	NS	S	S	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	USB 2.0 x 1 / Serial x 1	NS	NS	Cat 8	Cat 6	NS	NS	NS	NS	-40℃ - + 85℃	29 x 33 x 2.3	5	Voice (3G CS) /Data	https://www.gemalto.com/iot/iot-connectivity/products/iot-modules/pds6	Telit Wireless Solutions	Sales / Hideyuki Numata	+81-3-5412-7650
MM-MS0D	Seiko Solutions Inc.	-LTE(Cat.4)通信モジュール -通信速度(最大)DL150Mbps/UL50Mbps -UART, USB, Ethernet(サポート-端末/VoLTE), パケット通信, SMS, GNSS -安全生産対応に対応	2016年度	LTE/UMTS	M.2	Qualcomm	MDM9207-0		01.07.02	S	S	NS	S	S	NS	NS	NS	NS	S	S	NS	S	S	NS	USB2.0/UART/Ethernet / GPIO	NS	NS	Cat.10	Cat.6	Cat.4	NS	S	S	-20℃ - + 60℃	30 x 42 x 2.7	less than 7g	Voice (VoLTE, 3G CS) /Data	https://www.seiko-sol.co.jp/products/mm-ms0d/	セイコーソリューションズ株式会社	ICTイネルソリューション営業統括部MS営業部／営業大黒	043-211-1297
MM-MS1D	Seiko Solutions Inc.	-LTE(Cat.1)通信モジュール -通信速度(最大)DL10Mbps/UL5Mbps -UART, USB, Ethernet(サポート-端末/VoLTE), パケット通信, SMS, GNSS -安全生産対応に対応	2016年度	LTE only	M.2	Qualcomm	MDM9207-1		00.00.94	NS	NS	NS	NS	NS	NS	NS	NS	NS	S	S	NS	S	S	NS	USB2.0/UART/Ethernet / GPIO	NS	NS	NS	NS	Cat.1	NS	S	NS	-20℃ - + 60℃	30 x 42 x 2.7	less than 7g	Voice (VoLTE, 3G CS) /Data	https://www.seiko-sol.co.jp/products/mm-ms0d/	セイコーソリューションズ株式会社	ICTイネルソリューション営業統括部MS営業部／営業大黒	043-211-1297

本資料では弊社でTTP実施完了済みのメーカーブランド通信モジュール一覧の情報を掲載しております。
・記載情報は弊社がお客様向けに公開した製品のドキュメントブランド通信モジュールの情報です。
・掲載した情報は作成時点の情報であり、その後の変更・追加・廃止などの情報は反映されておりません。
・各資料に記載の製品仕様についてはモジュールベンダ様の情報を元に記載した情報です。
・弊社でその正確性を保証するものではございません。製品仕様についてはあるモジュールベンダ様にご確認をお願いします。